

Bảng thông số sản phẩm

Thông số kỹ thuật



APC Easy UPS On-Line SRV 3000VA RM 230V



SRV3KRI

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2400 W
Rated power in VA	3000 VA
Plug standard	IEC 60320 C20
Nb of power socket outlets	6 IEC 60320 C13 1 IEC 60320 C19
Number of rack unit	2U
Cable length	1.48 m
Number of cables	1
Provided equipment	Basic UPS signalling RS-232 cable CD with software Rack mounting brackets User manual USB cable

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	8.6 cm

Miễn trừ trách nhiệm: Tài liệu này không nhằm thay thế và không được sử dụng để xác định tính phù hợp hoặc độ tin cậy của các sản phẩm này cho các ứng dụng người dùng cụ thể

Width	43.7 cm
Depth	63.2 cm
Net weight	27.6 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
USB compatible	Yes
Mounting position	Horizontal

Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	72 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery life	3...5 year(s)
Battery charger power	60 W rated

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	29 kg
Package 1 Height	22.8 cm
Package 1 width	57.0 cm
Package 1 Length	79.4 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------