

Product datasheet

Specifications



APC Smart-UPS C 2000VA LCD 230V

SMC2000I

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	1300 W
Rated power in VA	2000 VA
Plug standard	IEC 320 C20
Nb of power socket outlets	6 IEC 320 C13 1 IEC 320 C19
Number of rack unit	0U
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD USB cable

General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Entry level
Redundant	No

Physical

Colour	Black
Height	21.6 cm
Width	17 cm
Depth	44 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	27.5 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	47...63 Hz

Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	2000 VA
Maximum configurable power in W	1300 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

Conformance

Product certifications	C-Tick CE EAC GOST SABS VDE
Equipment protection policy	3 years : \$250

Environmental

Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1

Battery life	3...5 year(s)
Battery power in VAH	499 VAh runtime
Battery charger power	166 W rated

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	Multifunction LCD status and control console
Free slots	0

Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	30 kg
Package 1 Height	33 cm
Package 1 width	37 cm
Package 1 Length	59 cm
Number of Units in Package 3	24

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------